

Cync Direct Connect Decorative Light Bulbs Specifications



Device

| Bulb Image |  |  |  |  |  |  |
|---------------------|---|---|---|--|---|---|
| Bulb Name | Direct Connect Full Color ST19 Light Bulb | Direct Connect Full Color G25 Light Bulb | Direct Connect Soft White ST19 Light Bulb | Direct Connect Soft White G25 Light Bulb | Direct Connect Full Color Decorative Medium Base Light Bulb | Direct Connect Full Color Decorative Candelabra Light Bulb |
| Lamp Description | CLEDST196CDGS | CLEDG256CDGS | CLEDST196LDGF | CLEDG256LDGF | CLEDBM6CDMS | CLEDBC6CDMS |
| Input Voltage | 120V | 120V | 120V | 120V | 120V | 120V |
| Lumens (Brightness) | 500 | 500 | 500 | 500 | 450 | 450 |
| Lumens per Watt | 80.6 | 80.6 | 83.3 | 83.3 | >80 | >80 |
| CRI | >90 | >90 | >90 | >90 | >90 | >90 |
| Lamp Equivalence | 60W | 60W | 60W | 60W | 40W | 40W |
| Life (Hours) | 15,000 | 15,000 | 15,000 | 15,000 | 15,000 | 15,000 |
| Line Frequency | 60Hz | 60Hz | 60Hz | 60Hz | 60Hz | 60Hz |
| CCT Range | 2000K - 7000K (2000K + RGB color mixing) | 2000K - 7000K (2000K + RGB color mixing) | 2700K | 2700K | 2000K - 7000K (2000K + RGB color mixing) | 2000K - 7000K (2000K + RGB color mixing) |
| Color Range | 16 Million Colors | 16 Million Colors | Soft White (2700K) | Soft White (2700K) | 16 Million Colors | 16 Million Colors |

Hardware

| | | | | | | |
|--------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Operating Temperature | -4°F to 104°F (-20°C to 40°C) |
| Base Type | E26 | E26 | E26 | E26 | E26 | E12 |
| Bulb Shape | ST19 | G25 | ST19 | G25 | BM | BC |
| MOL | 5.55in (141mm) | 5.00in (127mm) | 5.55in (141mm) | 5.00in (127mm) | 4.25in (108mm) | 4.09in (104mm) |
| MOD | 2.32in (59mm) | 3.18in (81mm) | 2.32in (59mm) | 3.18in (81mm) | 1.53in (39mm) | 1.53in (39mm) |
| Weight | 0.13lbs (60g) | 0.13lbs (60g) | 0.13lbs (60g) | 0.13lbs (60g) | 0.11lbs (50g) | 0.11lbs (50g) |
| Burn Position | Universal | Universal | Universal | Universal | Universal | Universal |
| Environmental (Wet, Dry, Damp) | Damp | Damp | Damp | Damp | Damp | Damp |
| Indoor/Outdoor | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor |

Electrical

| | | | | | | |
|---|---|---|---|---|---|---|
| Start Time | <1s | <1s | <1s | <1s | <1s | <1s |
| Standby Power | <0.2W | <0.2W | <0.2W | <0.2W | <0.2W | <0.2W |
| Power Factor | >0.7 | >0.7 | >0.7 | >0.7 | >0.7 | >0.7 |
| Power | 6W | 6W | 6W | 6W | 5.5W | 5.5W |
| Flickering Percentage | <30% @ 20% and 100% dimming @ default CCT | <30% @ 20% and 100% dimming @ default CCT | <30% @ 20% and 100% dimming @ default CCT | <30% @ 20% and 100% dimming @ default CCT | <30% @ 20% and 100% dimming @ default CCT | <30% @ 20% and 100% dimming @ default CCT |
| Short Term Flicker Perceptibility (PST) | <0.7 @ 10% dimming level |
| Stroboscopic Visibility Measure (SVM) | <1.6 @ 10% dimming level |
| Audible Noise | 20dB @ 30cm |

| | Direct Connect Full Color ST19 Light Bulb | Direct Connect Full Color G25 Light Bulb | Direct Connect Soft White ST19 Light Bulb | Direct Connect Soft White G25 Light Bulb | Direct Connect Full Color Decorative Medium Base Light Bulb | Direct Connect Full Color Decorative Candelabra Light Bulb |
|--------------------------------------|---|---|---|---|---|---|
| Controls | | | | | | |
| Dimmable | Yes | Yes | Yes | Yes | Yes | Yes |
| Tunable | Yes | Yes | No | No | Yes | Yes |
| Dimmer Type | Dimmable though Cync App, Cync Remotes and Cync Dimmers | Dimmable though Cync App, Cync Remotes and Cync Dimmers | Dimmable though Cync App, Cync Remotes and Cync Dimmers | Dimmable though Cync App, Cync Remotes and Cync Dimmers | Dimmable though Cync App, Cync Remotes and Cync Dimmers | Dimmable though Cync App, Cync Remotes and Cync Dimmers |
| Wireless | Yes | Yes | Yes | Yes | Yes | Yes |
| Wireless Protocol | Wi-Fi (2.4 GHz) and BLE |
| Mobile Compatibility | Works with iOS 13 and above and Android 9 and above | Works with iOS 13 and above and Android 9 and above | Works with iOS 13 and above and Android 9 and above | Works with iOS 13 and above and Android 9 and above | Works with iOS 13 and above and Android 9 and above | Works with iOS 13 and above and Android 9 and above |
| Voice Assistant Compatibility | Works with Google Home and Amazon Alexa |
| Reliability and Warranty | | | | | | |
| Warranty | 3 Years |
| Warranty Operating Conditions | Voltage: 120Vac/60hz; Temperature: -4°F to 104°F (-20°C to 40°C); Relative Humidity: < 88% 32°C | Voltage: 120Vac/60hz; Temperature: -4°F to 104°F (-20°C to 40°C); Relative Humidity: < 88% 32°C | Voltage: 120Vac/60hz; Temperature: -4°F to 104°F (-20°C to 40°C); Relative Humidity: < 88% 32°C | Voltage: 120Vac/60hz; Temperature: -4°F to 104°F (-20°C to 40°C); Relative Humidity: < 88% 32°C | Voltage: 120Vac/60hz; Temperature: -4°F to 104°F (-20°C to 40°C); Relative Humidity: < 88% 32°C | Voltage: 120Vac/60hz; Temperature: -4°F to 104°F (-20°C to 40°C); Relative Humidity: < 88% 32°C |
| Certifications | | | | | | |
| Safety Listing | UL 1993 |
| Lighting Facts | Yes | Yes | Yes | Yes | Yes | Yes |
| CEC Certification | Title 20 |