

# Full Color Dynamic Effects Smart Hexagon Panels Specifications



## Device

### Product Image



Product Name	Full Color Dynamic Effects Smart Hexagon Panels (7 Pack)	Full Color Dynamic Effects Smart Hexagon Panels (10 Pack)	Full Color Dynamic Effects Hexagon Expand Kit (5 Pack)
Description	CFIXTIHC DEN	CFIXTIHC DEN	CFIXTIHC DEN
Number of Panels	7	10	5
Box Contents	<ul style="list-style-type: none"> <li>(7) Smart Hexagon Panels</li> <li>(7) Templates</li> <li>(6) Linking cables</li> <li>(21) Traceless nails</li> <li>(1) Control box</li> <li>(1) Power adapter</li> <li>(1) Orientation piece</li> <li>(9) Adhesive strips</li> <li>(1) Mini level</li> <li>(1) Removal tool</li> <li>(2) Self-tapping screws</li> <li>(1) Cleaning wipe</li> </ul>	<ul style="list-style-type: none"> <li>(10) Smart Hexagon Panels</li> <li>(10) Templates</li> <li>(9) Linking cables</li> <li>(30) Traceless nails</li> <li>(1) Control box</li> <li>(1) Power adapter</li> <li>(1) Orientation piece</li> <li>(12) Adhesive strips</li> <li>(1) Mini level</li> <li>(1) Removal tool</li> <li>(2) Self-tapping screws</li> <li>(1) Cleaning wipe</li> </ul>	<ul style="list-style-type: none"> <li>(5) Smart Hexagon Panels</li> <li>(5) Templates</li> <li>(5) Linking cables</li> <li>(15) Traceless nails</li> <li>(6) Adhesive strips</li> <li>(1) Cleaning wipe</li> </ul>
Maximum Supported Panel Exention Quantity	20	20	N/A
Life (Hours)	25,000	25,000	25,000
CCT Range	2000K - 7000K	2000K - 7000K	2000K - 7000K
Color Range	16 Million Colors	16 Million Colors	16 Million Colors

## Hardware

Shape	Hexagon	Hexagon	Hexagon
Operating Temperature	-4°F to 104°F (-20°C to 40°C)	-4°F to 104°F (-20°C to 40°C)	-4°F to 104°F (-20°C to 40°C)
Panels Weight	3.53lbs (1600g)	4.85lbs (2200g)	0.22lbs (1000g)
Panel Dimensions (LxWxD)	7.08 x 6.14 x 0.69 in (180 x 156 x 17.5 mm) per panel	7.08 x 6.14 x 0.69 in (180 x 156 x 17.5mm) per panel	7.08 x 6.14 x 0.69 in (180 x 156 x 17.5mm) per panel
Adapter Dimensions (LxWxD)	3.04 x 1.86 x 2.09 in (77.1 x 47.3 x 53.1 mm)	3.04 x 1.86 x 2.09 in (77.1 x 47.3 x 53.1 mm)	N/A
Control Box Dimensions (LxWxD)	4.65 x 1.54 x 0.67 in (118 x 39 x 17 mm)	4.65 x 1.54 x 0.67 in (118 x 39 x 17 mm)	N/A
Linking Cable Dimensions (LxWxD)	5.31 x 0.40 x 0.28 in (135 x 10.5 x 7.2 mm)	5.31 x 0.40 x 0.28 in (135 x 10.5 x 7.2 mm)	N/A
Finish	White	White	White
Environmental (Wet, Dry, Damp)	Dry	Dry	Dry
Indoor/Outdoor	Indoor	Indoor	Indoor

## Certifications

FCC ID	PUU-TILE-CDEN	PUU-TILE-CDEN	PUU-TILE-CDEN
IC ID	10798A-CDENTILE	10798A-CDENTILE	10798A-CDENTILE
Safety Listing	UL153 and cUL153	UL153 and cUL153	UL153 and cUL153
Safety Listing for Adapter	UL1310 and cUL1310	UL1310 and cUL1310	UL1310 and cUL1310
Lighting Facts	Yes	Yes	Yes

## Electrical

<b>Input Voltage</b>	120V	120V	120V
<b>Line Frequency</b>	60Hz	60Hz	60Hz
<b>Adapter Input Voltage</b>	24V	24V	N/A
<b>Adapter Output Current</b>	1.5A	1.5A	N/A
<b>Lumens (Brightness)</b>	700	700	700
<b>Start Time</b>	1.5s	1.5s	1.5s
<b>Power Factor</b>	0.5	0.5	0.5
<b>Power</b>	40W @ 7000K 25W @ Red, Green, Blue	40W @ 7000K 25W @ Red, Green, Blue	40W @ 7000K 25W @ Red, Green, Blue
<b>Audible Noise</b>	20dB @ 30cm	20dB @ 30cm	

## Controls

<b>Dimmable</b>	Yes	Yes	Yes
<b>Dimmer Type</b>	Dimmable through Cync App, Cync Remotes and Cync Dimmers	Dimmable through Cync App, Cync Remotes and Cync Dimmers	Dimmable through Cync App, Cync Remotes and Cync Dimmers
<b>Light Shows</b>	Yes	Yes	Yes
<b>Music Sync</b>	Yes	Yes	Yes
<b>Wireless</b>	Yes	Yes	Yes
<b>Wireless Protocol</b>	Wi-Fi (2.4 GHz) and BLE	Wi-Fi (2.4 GHz) and BLE	Wi-Fi (2.4 GHz) and BLE
<b>Mobile Compatibility</b>	Works with iOS 13 and above and Android 9 and above	Works with iOS 13 and above and Android 9 and above	Works with iOS 13 and above and Android 9 and above
<b>Voice Assistant Compatibility</b>	Works with Google Home and Amazon Alexa	Works with Google Home and Amazon Alexa	Works with Google Home and Amazon Alexa

## Reliability and Warranty

<b>Warranty</b>	3 Years	3 Years	3 Years
<b>Warranty Operating Conditions</b>	Voltage: 120Vac/60hz; Temperature: -4°F to 104°F (-20°C to 40°C); Relative Humidity: < 80% 32°C	Voltage: 120Vac/60hz; Temperature: -4°F to 104°F (-20°C to 40°C); Relative Humidity: < 80% 32°C	Voltage: 120Vac/60hz; Temperature: -4°F to 104°F (-20°C to 40°C); Relative Humidity: < 80% 32°C

## Device Overview

### (A) Adapter

<b>On/Off</b>	Toggles the light strip on/off Hold for 10 seconds to reset
---------------	--

### (B) Control box

<b>Color Control</b>	Cycles through colors
<b>Light Effects</b>	Cycles through Light Shows and Music Sync presets

### (C) Hexagon Panel

